



TECHNICAL DATA SHEET

LANDORA BOAT VARNISH

Landora Boat Varnish is suitable for all woodwork in new and old boats. Landora Boat Varnish has a water-repellent and weather-resistant finish that is resistant to cracking. Landora Boat Varnish may also be used indoors, for example on door sills or other surfaces where a durable surface is desirable.

Environmental considerations: Surplus varnish is not to be disposed of in common drains. This material and its container must be disposed of as hazardous waste.

Directions for use

Stir thoroughly before use.

1. Sand the surface using a coarse grade paper. Scrape off any loose varnish and wipe the surface with a damp cloth.
2. At the first application the varnish should be diluted with 15-25% Landora Odorless Mineral Spirit. The following coats are applied using undiluted Landora Boat Varnish until the desired result is achieved.

The master painter suggests: Do not work in strong sunshine, and protect the varnished surface against dew until it is dry. The drying time of each coat is reduced if you only apply a thin coat each time. Several thin coats and sanding with very fine grit between each new coat will produce the best results.

Technical data:

Gloss Level: Very gloss (90).

Consumption: approx. 10 m²/litre.

Drying time at 20°C: Dry to the touch after approx. 4 hours, sandable after approx. 24 hours.

Application: Brush, roller or spraygun.

Cleaning of tools: Landora Odorless Mineral Spirit.

VOC limit value (Cat A/i): 500 g/l (2010).

Product VOC: < 500 g/l. **MAL code 1993:** 2-1.

White spirit based

TO BE STORED AWAY FROM FROST

KEEP OUT OF REACH OF CHILDREN

The product is available in the following amounts:

0.75 litre: Clear

