



TECHNICAL DATA SHEET

LANDORA CEILING & PANEL PAINT

For painting ceilings and panels of wood, MDF, particle board or veneer as well as for moldings, door frames, furniture and other woodwork.

Good adhesion and coverage, results in an even and matte finish. Suitable both as a primer and top coat.

Directions for use:

Stir thoroughly. Glossy surfaces must be roughened before painting.

1. Clean the surface with Landora Paint Wash and wipe it with a clean cloth. Prepare the surface by filling and sanding.
2. Apply 2 coats of Landora Ceiling & Panel Paint.

Tip: Knots in the wood may be sealed using Landora Knot Varnish to avoid any seeping through the paint.

Gloss Level: Matte (3).

Consumption: approx. 5-8 m²/litre.

Drying time: approx. 1-2 hours. Second coat may be applied after approx. 6 hours.

Application: Brush, roller or spray gun.

Cleaning of tools: Soap and water.

Environmental considerations: Surplus paint is not to be disposed of in common drains. Surplus paint, the container and any cleaning liquid is to be handed in to your local recycling station.

TO BE STORED AWAY FROM FROST

KEEP OUT OF REACH OF CHILDREN

The product is available in the following amounts:

0.75L Matte White

2.5L Matte White



Produced for the Landora brand.

Manufacturer: Hagmans Nordic AB, SE-511 10 Fritsla, Sweden.

Contact: +46-320-189 00

landora.com