



TECHNICAL DATA SHEET

LANDORA CEILING PAINT 03

Acrylate latex based paint with good coverage, suitable for ceilings.
NB! We recommend Landora Wall Paint 20 for ceilings in kitchens and bathrooms.

Directions for use:

Stir thoroughly.

Unpainted surfaces

1. Fill and sand the surface.
2. Apply 2 coats of Landora Ceiling Paint 03.

Previously painted surfaces

1. Clean the surface with Landora Paint Wash and wipe it with a clean cloth.
2. Fill and sand the surface.
3. Apply 2 coats of Landora Ceiling Paint 03.

Tip: Always start with the ceiling if you intend to paint the walls as well.
Use plenty of paint on the roller to avoid having streaks of paint.

Gloss Level: Matte (3).

Consumption: approx. 6 m²/litre.

Drying time at 20°C: approx. 1 hour. The second coat may be applied after approx. 3 hours.

Application: Brush, roller or spray gun.

Cleaning of tools: Soap and water.

Environmental considerations: Surplus paint is not to be disposed of in common drains. Surplus paint, the container and any cleaning liquid is to be handed in to your local recycling station.

TO BE STORED AWAY FROM FROST

KEEP OUT OF REACH OF CHILDREN

The product is available in the following amounts:

4L and 10L White



Produced for the Landora brand.

Manufacturer: Hagmans Nordic AB, SE-511 10 Fritsla, Sweden.

Contact: +46-320-189 00

landora.com