



TECHNICAL DATA SHEET

LANDORA CELLAR & STORAGE

Acrylate latex based paint, pervious and suitable for cellars, garages and storage rooms. The paint breathes and is suitable for application of concrete, plaster, autoclaved aerated concrete and plasterboard in spaces with high humidity.

Directions for use:

Stir thoroughly. Surfaces painted with lime paint or distemper must be thoroughly cleaned before application of the product.

Unpainted surfaces

1. Clean the surface.
2. Apply 2 coats of Landora Cellar & Storage.

Previously painted surfaces

1. Clean the surface with Landora Paint Wash and wipe it with a clean cloth.
2. Apply 2 coats of Landora Cellar & Storage.

Tip: The result of the application will be evident first when fully dry.

Technical data:

Gloss Level: Flat Matte (2).

Consumption: approx. 6-8 m²/litre.

Drying time at 20°C: approx. 1 hour. The second coat may be applied after approx. 3 hours.

Application: Brush, roller or spray gun.

Cleaning of tools: Soap and water.

TO BE STORED AWAY FROM FROST

KEEP OUT OF REACH OF CHILDREN

Environmental considerations: Surplus paint is not to be disposed of in common drains. Surplus paint, the container and any cleaning liquid is to be handed in to your local recycling station.

The product is available in the following amounts: 4L and 10L White



Produced for the Landora brand.

Manufacturer: Hagmans Nordic AB, SE-511 10 Fritsla, Sweden.

Contact: +46-320-189 00

landora.com