

TECHNICAL DATA SHEET

LANDORA CHINESE WOOD OIL

High quality Chinese wood oil, gives good protection to all sorts of wood. Landora Chinese Wood Oil is extremely penetrating and is resistant to discolouring and cracking.

It can be used both indoor and outdoor, and is suitable for furniture, floors, windows, panelling and other woodwork.

The wood oil give a nice sheen to floor tiles.

Environmental considerations: Surplus oil is not to be disposed of in common drains. Surplus product, the container and any cleaning liquid is to be treated as dangerous goods and handed in to your local recycling station.

Directions for use

1. Make sure the surface is solid, dry and well cleaned with a wire brush or by sanding.
2. Apply Landora Chinese Wood Oil generously with a brush or cloth until the surface stops absorbing the oil.
If using a spray can: Shake the can thoroughly, spray on and even out using a cloth.
3. Important: Wipe off any excess oil with a clean cloth after approx. 20-30 minutes.
4. Leave the oil to dry for 24 hours between each application. Apply at least 2 coats to untreated wood. Many applications will produce a surface comparable to varnish.

The paint master says: Drying time depends on the state of the surface. A dry surface may require several coats of oil, whereas a surface that is already saturated will require much less. Test as you proceed, and carefully wipe off any surplus oil in order to avoid having a tacky or spotted surface.

Technical data:

Consumption: 3-9 m²/litre.

Drying time at 20°C: at least 24 hours.

Application: Brush, cloth or spray gun.

Cleaning of tools: Landora Mineral Spirit or other white spirit.

VOC limit value (Cat A/f): 700 g/l (2010).

Product VOC: < 700 g/l.

White spirit based

TO BE STORED AWAY FROM FROST

KEEP OUT OF REACH OF CHILDREN

The product is available in the following amounts:

0.75 litre: Clear

