



TECHNICAL DATA SHEET

LANDORA DOOR & WINDOW PAINT

Used for painting windows, doors, garden furniture and other outdoor woodwork. Easy to apply with good flow and adhesion. Provides a hard and durable surface with good resistance to mold and algae.

Do not paint in direct sunlight or if there is a risk for dew.

Factory painted surfaces: first paint a smaller part to be able to determine the adhesive effect.

Directions for use:

1. Wash with Landora Facade Cleaner (protect the windows). Rinse carefully and make sure the surface is dry and well cleaned. If the surface has been painted previously, remove any loose paint and sand the surface to a dull sheen.
2. Unpainted wood must be treated with Landora Primer Oil. Make sure that end pieces have a generous coat. (Windows should be painted before you insert the windowpanes)
3. Fill any cracks with Landora Window Putty.
4. Apply Landora Wood Primer
5. Apply putty where needed once the primer has dried.
6. Finish off by applying 2 coats of Landora Door & Window Paint.

Tip: Paint connected areas in one go, and take a break only when you have arrived at a corner.

Technical data:

Gloss Level: Gloss (50).

Consumption: approx. 6-8 m²/litre.

Application: Brush, roller or spraygun.

Drying time: Dry to the touch after approx. 4 hours. Second coat may be applied after approx. 12 hours at 20°C.

Dilution/Cleaning: Landora Mineral Spirit

Water based

TO BE STORED AWAY FROM FROST

KEEP OUT OF REACH OF CHILDREN

The product is available in the following amounts:

0.75 litre: White

2.5 litre: White



Produced for the Landora brand.

Manufacturer: Hagmans Nordic AB, SE-511 10 Fritsla, Sweden.

Contact: +46-320-189 00

landora.com