



TECHNICAL DATA SHEET

LANDORA KITCHEN & BATH

Water based acrylate paint for walls and ceilings in bathrooms, kitchens, wash-rooms and other spaces where a wear-resistant and durable surface is desirable. The paint will dry having an impervious layer that prevents the penetration of water. Washable.

NB! Not suitable for showers or on surfaces in direct contact with water.

Directions for use:

Stir thoroughly. If you are painting on a wall with PVC, the surface must be thoroughly cleaned with denatured alcohol in order to remove any remaining plasticizer.

Wet spaces

1. Clean the surface with Landora Paint Wash. Use a descaling agent around wash basins.
2. Apply wet room putty on uneven patches. Sand.
3. Apply 2 coats of Landora Kitchen & Bath.

Other spaces

1. Clean the surface thoroughly. 2. Apply 2 coats of Landora Kitchen & Bath.

Tip: The paint is full impermeable after about a week. Try to avoid splashing the surface before that time.

Gloss Level: Semigloss (25).

The paint is enough for: approx. 20 m².

Consumption: approx. 5-8 m²/litre.

Drying time at 20°C: approx. 1 hour. The second coat may be applied after approx. 8 hours.

Application: Brush, roller or spray gun.

Cleaning of tools: Soap and water.

KEEP OUT OF REACH OF CHILDREN

Environmental considerations: Surplus paint is not to be disposed of in common drains.

Surplus paint, the container and any cleaning liquid is to be handed in to your local recycling station.

The product is available in the following amounts:

2.5L White



Produced for the Landora brand.

Manufacturer: Hagmans Nordic AB, SE-511 10 Fritsla, Sweden.

Contact: +46-320-189 00

landora.com