



TECHNICAL DATA SHEET

LANDORA PANEL VARNISH

Semi-gloss, acrylate latex based varnish for wood panels. The treated surface is resistant to water, grease and household chemicals. It is also suitable for protecting walls of brick, concrete, plaster or wallpaper.

Directions for use:

Stir thoroughly.

1. Clean the surface thoroughly.
2. Apply 1 coat of Landora Panel Varnish. Let dry.
3. Sand lightly with fine-grit sanding paper.
4. Apply a final coat of varnish.

Tip: Apply with even and long strokes along the entire length of the panel, and avoid any overlaps.

Technical data:

Gloss Level: Semigloss (20).

Consumption: approx. 10 m²/litre.

Drying time: approx. 1 hour. Second coat may be applied after approx. 2 hours.

Application: Large varnish brush (70 mm).

Cleaning of tools: Soap and water.

Environmental considerations: Surplus paint is not to be disposed of in common drains. Surplus paint, the container and any cleaning liquid is to be handed in to your local recycling station.

TO BE STORED AWAY FROM FROST

KEEP OUT OF REACH OF CHILDREN

The product is available in the following amounts:

0.75L and 2.5L Chalky white



Produced for the Landora brand.

Manufacturer: Hagmans Nordic AB, SE-511 10 Fritsla, Sweden.

Contact: +46-320-189 00

landora.com