



TECHNICAL DATA SHEET

LANDORA PLASTER PAINT

Suitable for painting on plastered surfaces both indoor and outdoor.

Pervious plaster paint with good covering properties, resistant to fading. Permits the surface to breathe and lowers the risk of frost damage.

NB! New grout must dry for 4 to 6 weeks before you apply the paint. Do not paint of a surface heated by sunlight or late in the day if there is a risk for dew. Can be used on surfaces that were previously painted with silicate paint.

Directions for use:

Stir thoroughly. If you have to stop application of the paint, stop in a corner or at a joint.

Unpainted grout or concrete:

1. Brush off loose particles. Mend any crack or hole.
2. Apply 2 coats of Landora Plaster Paint.

Previously painted surfaces:

1. Remove any loose grout or paint. Mend any crack or hole. Wash with Landora Facade Cleaner (remember to protect the windows). Rins with water. Leave to dry thoroughly.
2. Apply 2 coats of Landora Plaster Paint.

Tip: If the surface is very absorbent, apply first a coat of Landora Plaster Paint diluted with 20 % water. If the surface is powdery, prime it with Landora Primer Oil.

Gloss Level: Matte

Consumption: approx. 6 m²/litre.

Drying time at 20°C: approx. 4 hours. The second coat may be applied after approx. 12 hours.

Application: Brush, roller or spraygun.

Cleaning of tools: Soap and water.

Environmental considerations: Surplus paint is not to be disposed of in common drains. Surplus paint, the container and any cleaning liquid is to be handed in to your local recycling station.

TO BE STORED AWAY FROM FROST

KEEP OUT OF REACH OF CHILDREN

The product is available in the following amounts:

0.75L Slate, Black, White

2.5L House Gray, Slate, Black, White

10L White

