



TECHNICAL DATA SHEET

Landora Traditional Red Paint

Landora Traditional Red Paint is a covering, water-based emulsion paint with beautiful dark red pigments that is dull when dry. The paint allows the wood to breathe, which reduces the risk of rot and mildew. Landora Traditional Red Paint should only be used on new unplanned wood, or on surfaces previously painted with emulsion paints.

NB! Do not apply too much paint each time, since the paint will flake. Do not paint of a surface heated by sunlight or at temperatures below 5° C. The paint may flake if it dries too fast. If flaking occurs, scrape off the flakes and brush off any loose material. Then apply another layer, using diluted paint.

Minor differences in colour may occur with different batch numbers. If you have products with different batch numbers, we recommend that you mix the various batches to achieve uniformity.

Environmental considerations: Surplus paint is not to be disposed of in common drains. Surplus paint, the container and any cleaning liquid is to be handed in to your local recycling station.

Binder: Linseed oil up to 8 % total weight.

Contains an anti-mold agent.

Landora Traditional Red Paint is to be used within 12 months of purchase.

Directions for use

Stir thoroughly.

If there is mold or algae on the surface, wash with Landora Facade Cleaner (remember to protect windows and glass sections) and leave to dry for a minimum of 24 hours before painting. Nail heads must be covered with an anti-corrosion paint such as Landora Rust Primer in order to adhere properly. Knots and dried sap must be sanded or rasped.

Rain may carry off the paint before it is fully dried. Therefore you should cover windows, doors, drain pipes and the house foundations until the paint is fully dried.

New and untreated surface:

New and untreated wood must be treated with 14 days of erection.

1. Make sure the surface is clean and free from loose material. Remove all dust.
2. Apply a first coat of Landora Traditional Red Paint diluted with 20% water. Let dry for 24 hours.
3. Apply the second coat of Landora Traditional Red Paint. Start at the top and work your way down, wet in wet. Apply as thin a coat as possible until you have achieved a good cover.

Surfaces previously painted with emulsion paints:

1. Clean any dirt or loose paint from the surface using a broom or a wire brush. Use a mask. Finish off by brushing with a soft broom.
2. Apply a coat of Landora Traditional Red Paint. If the surface requires to have two coats, the first coat should be diluted with 20% water. Start at the top and work your way down, wet in wet. Apply as thin a coat as possible until you have achieved a good cover.

The master painter suggests: Apply the paint thinly and start at the top, working your way down. Use a large emulsion paint brush.

Produced for the Landora brand.

Manufacturer: Hagmans Nordic AB, SE-511 10 Fritsla, Sweden.

Contact: +46-320-189 00

landora.com



Technical data:

Consumption: approx. 2-3 m²/litre.

Drying time at 20°C: approx. 1 hour. The second coat may be applied after approx. 24 hours.

Application: Brush for emulsion paints.

Cleaning of tools/dilution: Water.

VOC limit value (Cat A/d): 130 g/l (2010).

Product VOC: < 130 g/l. **MAL code 1993:** 00-1.

Water based

TO BE STORED AWAY FROM FROST

KEEP OUT OF REACH OF CHILDREN

The product is available in the following amounts:

10.0 litres



Produced for the Landora brand.

Manufacturer: Hagmans Nordic AB, SE-511 10 Fritsla, Sweden.

Contact: +46-320-189 00

landora.com